


Airpocket Select Power

Product Range



Features



Applications



Filter Class



Coarse



KEY FACTS

- Synthetic filter media
- Long service life
- High dust holding capacity
- Suitable for air flows up to 4250 m³/h
- Low Pressure drop

DESIGN

Progressively-structured, polyester media. Conically sewn into single pockets and fitted into a robust plastic frame with integrated air guides.

APPLICATIONS

Prefiltration for gas turbine air intakes.

Airpocket Select Power

PERFORMANCE DATA

Article No.	Filter Class		Dimensions mm	Pockets	Flow Rate m ³ /h	Pressure Drop Pa
	ISO 16890	EN 779				
800321024387	Coarse 70%	G4	592 x 592 x 200	6	3400	40
800321024383	Coarse 70%	G4	592 x 592 x 300	6	3400	38
800321024384	Coarse 70%	G4	592 x 592 x 360	6	3400	35
800321024385	Coarse 70%	G4	592 x 592 x 500	6	3400	33
800321024386	Coarse 70%	G4	592 x 592 x 600	6	3400	30
800321024387	Coarse 80%	M5	592 x 592 x 200	6	3400	65
800321024388	Coarse 80%	M5	592 x 592 x 300	6	3400	62
800321024389	Coarse 80%	M5	592 x 592 x 360	6	3400	60
800321024390	Coarse 80%	M5	592 x 592 x 500	6	3400	55
800321024391	Coarse 80%	M5	592 x 592 x 600	6	3400	50

SPECIFICATION

Recommended air velocity	2.5 m/s ± 20 %	Recommended final pressure drop	250 Pa
Heat resistance	Max. 80 °C	Moisture resistance	100 % rel. humidity
Regenerable	No	Incinerable	Yes

OPTIONS

Gasket	EPDM flat gasket, 1 or 2 sides
Header depth	25 mm or 20 mm
Frame	Plastic or metal