

Airroll Select Dust Glass

Product Range



Select

Features



Applications



Filter Class

G

Coarse



KEY FACTS

- Glass fiber filter medium
- To separate dry dust
- Free of silicon and paint-damaging substances
- Resistant to acetone

DESIGN

Continuously-spun glass fiber filter mats, which are impregnated with an antibacterial dust adhesive. Media features a progressive structure to provide even dirt loading.

APPLICATIONS

Separation of dry dusts in metal working plants, wood shops, etc.

Airroll Select Dust Glass

PERFORMANCE DATA

Article No.	Filter Class		Dimensions	Air Velocity	Pressure Drop
	ISO 16890	EN 779	mm	m/s	Pa
800120029931	Coarse 60%	G3	500 x 20000 x 25	2	35
800121021955	Coarse 60%	G3	750 x 20000 x 25	2	35
800120029932	Coarse 60%	G3	1000 x 20000 x 25	2	35
800120029933	Coarse 60%	G3	1500 x 20000 x 25	2	35
800120029934	Coarse 60%	G3	500 x 20000 x 50	2	50
800121021954	Coarse 60%	G3	750 x 20000 x 50	2	50
800120029935	Coarse 60%	G3	1000 x 20000 x 50	2	50
800120029936	Coarse 60%	G3	1500 x 20000 x 50	2	50
800120029938	Coarse 70%	G3	500 x 20000 x 100	2	60
800121021956	Coarse 70%	G3	750 x 20000 x 100	2	60
800120029939	Coarse 70%	G3	1000 x 20000 x 100	2	60
800120029940	Coarse 70%	G3	1500 x 20000 x 100	2	60

SPECIFICATION

Recommended air velocity	2 m/s	Rec. final pressure for efficient energy use acc. to EN 13053	Lowest value of initial pressure drop + 50 Pa, or initial pressure drop x 3
Heat resistance	Max. 80 °C	Moisture resistance	100 % rel. humidity
Regenerable	No	Incinerable	No