

Airroll Select

Glass Automatic RFM

Product Range



Features



Applications



Filter Class

G

Coarse



KEY FACTS

- Compatible with CEAG and AAF roll filter systems
- High dust holding capacity
- Wound for standard or reverse flow
- Odor free

DESIGN

Continuously-spun glass fiber media, tension wound onto a steel spool with end plates.

APPLICATIONS

Replacement filter roll for installation in CEAG and AAF systems.

Airroll Select

Glass Automatic RFM

PERFORMANCE DATA

Article No.	Filter Class		Dimensions	Pressure Drop
	ISO 16890	EN 779		
			mm	Pa
800122027877	Coarse 70%	G3	526 x 20000 x 60	48
800122027878	Coarse 70%	G3	836 x 20000 x 60	48
800122027879	Coarse 70%	G3	1141 x 20000 x 60	48
800122027880	Coarse 70%	G3	1446 x 20000 x 60	48
800122027881	Coarse 70%	G3	1751 x 20000 x 60	48
800122027893	Coarse 70%	G3	2056 x 20000 x 60	48

SPECIFICATION

Recommended air velocity	2.5 m/s	Rec. final pressure for efficient energy use acc. to EN 13053	Lowest value of initial pressure drop + 50 Pa, or initial pressure drop x 3
Heat resistance	Max. 120 °C	Moisture resistance	80 %
Regenerable	No	Incinerable	No