

# Airroll Select

## Glass Automatic RFT

### Product Range



### Features



### Applications



### Filter Class

G

Coarse



### KEY FACTS

- Compatible with Trox automatic roll filter hardware
- High dust holding capacity
- Wound for standard or reverse flow
- Odor free

### DESIGN

Continuously-spun glass fiber media, tension wound onto a cardboard cassette with a metal shaft.

### APPLICATIONS

Replacement filter roll for installation in Trox systems.

# Airroll Select

## Glass Automatic RFT

### PERFORMANCE DATA

Article No.	Filter Class		Dimensions	Pressure Drop
	ISO 16890	EN 779	mm	Pa
800122027882	Coarse 70%	G3	650 x 20000 x 60	48
800122027883	Coarse 70%	G3	950 x 20000 x 60	48
800122027884	Coarse 70%	G3	1250 x 20000 x 60	48
800122027885	Coarse 70%	G3	1550 x 20000 x 60	48
800122027886	Coarse 70%	G3	1850 x 20000 x 60	48
800122027887	Coarse 70%	G3	2150 x 20000 x 60	48

### SPECIFICATION

<b>Recommended air velocity</b>	2.5 m/s	<b>Rec. final pressure for efficient energy use acc. to EN 13053</b>	Lowest value of initial pressure drop + 50 Pa, or initial pressure drop x 3
<b>Heat resistance</b>	Max. 120 °C	<b>Moisture resistance</b>	80 %
<b>Regenerable</b>	No	<b>Incinerable</b>	No