

# Airroll Select Paint Dust

## Product Range



Select

## Features



## Applications



## KEY FACTS

- Glass fiber filter medium
- To separate paint mists
- Free of silicon and paint-damaging substances
- Resistant to acetone

## DESIGN

Continuously-spun glass fiber filter mats with a progressive structure to provide even dirt loading.

## APPLICATIONS

Floor filter for color mist separation in paint cabins and spray booth in the automobile industry, body paint shops, carpentry workshops, etc.

# Airroll Select Paint Dust

## PERFORMANCE DATA

Article No.	Average arrestance	Dimensions	Air Velocity	Pressure Drop
	Paint mist (%)	mm	m/s	Pa
800121029922	90 – 95	500 x 20000 x <b>50</b>	2.5	30
800121021957	90 – 95	750 x 20000 x 50	2.5	30
800121029923	90 – 95	1000 x 20000 x 50	2.5	30
800121029924	90 – 95	1500 x 20000 x 50	2.5	30
800121029925	93 – 97	500 x 20000 x <b>70</b>	2.5	40
800121021958	93 – 97	750 x 20000 x 70	2.5	40
800121029926	93 – 97	1000 x 20000 x 70	2.5	40
800121029927	93 – 97	1500 x 20000 x 70	2.5	40
800121029928	98 – 99	500 x 20000 x <b>100</b>	2.5	60
800121021959	98 – 99	750 x 20000 x 100	2.5	60
800121029929	98 – 99	1000 x 20000 x 100	2.5	60
800121029930	98 – 99	1500 x 20000 x 100	2.5	60

## SPECIFICATION

<b>Recommended air velocity</b>	2.5 m/s	<b>Recommended final pressure drop</b>	80 Pa for 50 mm and 70 mm, 130 Pa for 100 mm
<b>Heat resistance</b>	Max. 180 °C	<b>Moisture resistance</b>	80 %
<b>Regenerable</b>	No	<b>Incinerable</b>	No

# Airroll Select Paint Dust

## Product Range



Select

## Features



## Applications



## KEY FACTS

- Glass fiber filter medium
- To separate paint mists
- Free of silicon and paint-damaging substances
- Resistant to acetone

## DESIGN

Continuously-spun glass fiber filter mats with a progressive structure to provide even dirt loading.

## APPLICATIONS

Floor filter for color mist separation in paint cabins and spray booth in the automobile industry, body paint shops, carpentry workshops, etc.

# Airroll Select Paint Dust

## PERFORMANCE DATA

Article No.	Average arrestance	Dimensions	Flow rate	Pressure Drop
	Paint mist (%)	mm	m/s	Pa
800121021957	90 - 95	750 x 20000 x 50	2.5	6 - 30
800121021958	93 - 97	750 x 20000 x 70	2.5	7 - 40
800121021959	98 - 99	750 x 20000 x 100	2.5	14 - 60

## SPECIFICATION

<b>Recommended air velocity</b>	2.5 m/s	<b>Recommended final pressure drop</b>	80 Pa for 50 mm and 70 mm, 130 Pa for 100 mm
<b>Heat resistance</b>	Max. 180 °C	<b>Moisture resistance</b>	80 %
<b>Regenerable</b>	No	<b>Incinerable</b>	No