

# Nanoclass Cube N Pro HT

## Product Range



## Features



## Applications



## Filter Class



## KEY FACTS

- For high flow rates up to 3,400 m<sup>3</sup>/h
- High temperature resistance up to 220 °C
- Compact, space-saving design
- Large active media area
- Rigid and robust

## DESIGN

V-shaped pleated cells with silicon-coated thread separators to ensure the even spacing of the pleats. Sealed with silicon in a stainless steel case. Integrated handle for ease of installation.

## APPLICATIONS

HEPA filters for terminal outlets in ventilation and clean room systems with high air quantities.

# Nanoclass Cube N Pro HT

## PERFORMANCE DATA

Article No.	Filter Class	Dimensions	Flow Rate	Pressure Drop
	<b>EN 1822</b>	<b>mm</b>	<b>m<sup>3</sup>/h</b>	<b>Pa</b>
800511000350	H13	610 x 610 x 292	3400	270

## SPECIFICATION

<b>Recommended air flow</b>	Flow rate $\pm$ 10 %	<b>Recommended final pressure drop</b>	450 Pa (max. 600 Pa)
<b>Heat resistance</b>	Max. 220 °C	<b>Moisture resistance</b>	100 % rel. humidity
<b>Regenerable</b>	No	<b>Incinerable</b>	No

## OPTIONS

<b>Gasket</b>	Silicon gasket, 1 or 2 sides
---------------	------------------------------