

# Baldwin - Spin-on Coolant Filters with BTA PLUS Formula | #BW5073

[☰ View Series Page](#)



## Local Contact

### Parker Sales Company UK

Tachbrook Park Drive

Tachbrook Park

Warwick

United Kingdom

CV34 6TU

### Phone

+44 (0)1926 317878

**Get your Parker account Today!**

Create one account to manage everything you do with Parker, from your shopping preferences to your application access.

[Register now](#)

The objective of diesel engine coolant filters, also known as water filters, is to remove contaminants from the engine cooling system and add chemicals to the coolant itself to replenish important protectants that may be lost over time.

[Share / Email](#)

## Technical Specifications

**Product Type:**

Coolant Spin-on with BTA PLUS Formula

**Notes:**

Maintenance filter for systems with 22-32 gallons capacity.; Can be used with CFB5000 base or CFB8784 dual base.

**Contains:**

8 Units BTA PLUS

**Thread Size:**

11/16-16

**Outside Diameter:**

3 11/16 (93.7)

**Length:**

5 3/8 (136.5)

**Includes:**

I. Gasket: G381-A

**Micron Rating:**

20 Nominal; 45 Absolute

**Compatible Competitor Part Number:**

Agco 1076751M1; Case 690139C1; Caterpillar 226-6567; Cummins 3315115; Daewoo 9912-15115; Demag 692336; Hitachi 19305494; Versatile 104040; Volvo M12968028; Fleetguard WF2073

**Application:**

Cummins Engines

**Brand:**

Baldwin

**Industry:**

On Highway Trucks

## Item Information

The objectives of diesel engine coolant filters, also known as water filters, are to remove contaminants from the engine cooling system and add chemicals to the coolant itself to replenish important protectants that may be lost over time. Baldwin Filters offers a complete line of Supplemental Coolant Additives (SCAs) and products to help you maintain your diesel engine cooling system. Baldwin's coolant spin-on filters with Balanced Treatment Additive (BTA PLUS) are designed to protect the engine and enhance its performance. BTA PLUS is a phosphate/molybdate/nitrite-based inhibitor designed for use in plain water or in up to 60 percent antifreeze solutions.

— Show Less

---

# CAD Drawings + Files

No CAD files available

---

---