

# Baldwin - Diesel Fuel Filter Elements | #PF312\_Baldwin

[☰ View Series Page](#)



## Local Contact

### Parker Sales Company UK

Tachbrook Park Drive

Tachbrook Park

Warwick

United Kingdom

CV34 6TU

### Phone

+44 (0)1926 317878

Get your Parker account Today!

Create one account to manage everything you do with Parker, from your shopping preferences to your application access.

[Register now](#)

Modern fuel injection systems require fuel be free of both particulate and water contamination. Baldwin fuel filters keep fuel clean and engines running at maximum efficiency.

[Share / Email](#)

## Technical Specifications

**Product Type:**

Primary Fuel Element

**Outside Diameter:**

3 23/32 (94.5)

**Inside Diameter:**

1/2 (12.7) & 1 1/32 (26.2)

**Length:**

7 17/32 (191.3)

**Includes:**

F. Gasket: AL6G480; End Seals: [1] Attached; Grommets: [1] Attached

**Micron Rating:**

9 Nominal; 25 Absolute

**Compatible Competitor Part Number:**

Allis Chalmers 4964323; Fiat 1902096; Iveco 1902096

**Application:**

Allis Chalmers, Fiat-Allis, New Holland Equipment; Iveco Trucks

**Brand:**

Baldwin

**Division:**

Engine Mobile Aftermarket

**Industry:**

Agriculture, Automotive, Commercial trucks and buses, Construction, Heavy-duty on-highway transportation, Industrial, Locomotive, Marine, Mining, Oil & Gas, Power Generation

**Technology:**

Filtration

## Item Information

"Modern fuel injection systems require fuel be free of both particulate and water contamination. Baldwin fuel filters keep fuel clean and engines running at maximum efficiency. New fuel systems operate at higher pressures (up to 60,000 psi) and tighter tolerances than ever before. Microscopic particles in the fuel, as small as 2-3 microns, can cause abrasive wear severely damaging the fuel injection system and other high pressure engine components. Baldwin Filters offers more than 1100 different fuel filters, fuel managers, coalescers, and fuel/water separators to protect your engine

[— Show Less](#)

# CAD Drawings + Files

No CAD files available

---

---