Fleetguard® Product Specification

AH19261

Air Housing

Fleetguard® AH19261 has revolutionized air filtration design with the introduction of its patented Fleetguard® OptiAir[™] technology. To fit shrinking engine compartments, OptiAir has a reduced system size. The two-stage air housing design extends filter life and lowers restriction to deliver maximum engine performance. Higher dust holding capacity allows for longer service intervals and lower maintenance costs.



Height	412.70 mm
Overall Width	237.50 mm
Length	278.20 mm
Inlet Diameter	95.25 mm
Inlet Length	95.25 mm
Largest housing OD	237.57 mm
Outlet Diameter	101.60 mm

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved