



# Product Specification

## AS2274

Air/Oil Separator

Fleetguard® AS2274 air oil separator prevents oil build-up, protects against detonation, and minimizes oil loss which equates to reduced maintenance and more consistent performance.



<b>End 2 ID</b>	96.77 mm
<b>End 1 ID</b>	96.77 mm
<b>Thread Pitch</b>	0.00 mm
<b>Length</b>	0.00 mm
<b>Largest ID</b>	96.77 mm
<b>Largest OD</b>	0.00 mm
<b>End 2 OD</b>	174.75 mm
<b>Thread Diameter</b>	0.00 mm

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved