

FF256

Fuel

Fleetguard® FF256 spin-on fuel filter that include NanoNet® high-performance filtration media reduce the number of harmful particles in the engine's fuel injectors. Its unique design delivers maximum engine life with premium protection and longer filter life, minimizing your operating costs.



Length	306.00 mm
Thread Diameter	110.00 mm
Anti Drain Back Valve	No
Media Type	NanoNet
Thread Form	Metric
Largest OD	138.18 mm
Thread Pitch	2.50 mm
Gasket Inside Diameter	118.96 mm
Gasket OD	138.18 mm
Hydrostatic Burst Minimum	175 PSI
Thread Class	7H
Thread Type	Internal
Flow Direction	Outside In
Particle Size at Beta 10 (Multi Pass)	4 micron
Particle Size at Beta 100 (Multi Pass)	4 micron
Particle Size at Beta 1000 (Multi Pass)	4 micron
Particle Size at Beta 10000 (Multi Pass)	4 micron

Particle Size at Beta 200 (Multi Pass) 4 micron
Particle Size at Beta 4000 (Multi Pass) 4 micron
Particle Size at Beta 500 (Multi Pass) 4 micron
Thread Seal Type Internal

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved