

(<https://www.cumminsfiltration.com/>)

~~(<https://www.cumminsfiltration.com/>)~~

Part Information

[Back \(CatalogSearch.do?&criteria=part\)](#)



FF270

Fuel

Add To Worksheet

Note: All parts are not available in all regions of the world. Contact your [Customer Assistance Center](https://www.cumminsfiltration.com/customerassistance) (<https://www.cumminsfiltration.com/customerassistance>) to ensure availability.

Export As...

Attributes	
Overall Height	71.88 mm (2.83 inch)
Largest OD	93.98 mm (3.7 inch)
Gasket OD	65.53 mm (2.58 inch)
Gasket Inside Diameter	2.25 in
Thread Pitch	1.5 mm per Thread
Thread Diameter	20 mm (.787 inch)
Thread Class	6H
Thread Form	Metric
Flow Direction	Outside In
Hydrostatic Burst Minimum	200 PSI
Free Water Separation	0.0
Primary Applications	
11980255801 YANMAR /catalog/CatalogSearch.do?partNumber_PartDeatils=11980255801	All Applications (/catalog/CatalogSearch.do?partNumber_PartDeatils=FF270)



◆ 2022 Cummins Filtration

[PRIVACY POLICY \(HTTPS://WWW.CUMMINSFILTRATION.COM/PRIVACY\)](https://www.cumminsfiltration.com/privacy) | [TERMS AND CONDITIONS](https://www.cumminsfiltration.com/terms-and-conditions)

[\(HTTPS://WWW.CUMMINSFILTRATION.COM/TERMS-AND-CONDITIONS\)](https://www.cumminsfiltration.com/terms-and-conditions) | [COOKIES](https://www.cumminsfiltration.com/cookies)

[\(HTTPS://WWW.CUMMINSFILTRATION.COM/COOKIES\)](https://www.cumminsfiltration.com/cookies) | [SITE MAP \(HTTPS://WWW.CUMMINSFILTRATION.COM/SITEMAP\)](https://www.cumminsfiltration.com/sitemap)