

FF5019

Fuel, Spin-On

Fleetguard® FF5019 premium spin-on fuel filter delivers superior performance using proven media technology, removing harmful contaminants. Fleetguard fuel filters ensure optimal fuel system protection to meet or exceed OEM specifications.



Gasket OD	71.27 mm
Gasket Inside Diameter	62.23 mm
Length	181.23 mm
Largest OD	107.67 mm
Thread Size	7/8-14 UNF-2B
Seam OD	108.20 mm
Standpipe	NO
EFFICIENCY, TWA BY SAE J 1858	99%
EFFICIENCY, TWA BY SAE J 1985	99%
MICRON RATING BY SAE J 1858	20 micron
MICRON RATING BY SAE J 1985	20 micron

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved