

FF5094

Fuel, Spin-On

Fleetguard® FF5094 spin-on fuel filter delivers superior performance using proven media technology, removing harmful contaminants. Fleetguard fuel filters ensure optimal fuel system protection to meet or exceed OEM specifications.

20 micron



MICRON RATING BY SAE J 1858

Gasket OD 71.63 mm **Gasket Inside Diameter** 62.59 mm 3/4-16 UNF-2B Thread Size 107.67 mm **Largest OD** 168.55 mm Length Seam OD 108.20 mm NO **Standpipe EFFICIENCY, TWA BY SAE J 1858** 97%

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved