



Product Specification

FF5373

Fuel, Spin-On

Fleetguard® FF5373 premium spin-on fuel filter delivers superior performance using proven media technology, removing harmful contaminants. Fleetguard fuel filters ensure optimal fuel system protection to meet or exceed OEM specifications.



Gasket Inside Diameter	62.50 mm
Gasket OD	72.50 mm
Largest OD	88.00 mm
Length	99.00 mm
Thread Pitch	1.50 mm
Thread Form	Metric
Thread Diameter	12.00 mm
Hydrostatic Burst Minimum	1200 kPa
Thread Class	6H
Thread Type	Internal
Flow Direction	Outside In
Thread Seal Type	Internal

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved