




Product Specification

FH23900

FUEL HOUSING

As part of Industrial Pro®FH239 series, the Fleetguard® FH23900 is designed for off-road equipment, construction, agricultural, mobile or stationary applications. Available in a wide range of configurations and specifications such as water-in-fuel (WIF) sensors, improved drain valves, electric priming pumps, priming ports, lighter cast aluminum construction, and low restriction check valve, designed to be the ultimate in fuel/water separation for diesel engines. It combines EleMax™ filter technology and multi-layered NanoNet® media, protecting against shorter filter life and potential fuel system damage caused by water or particle contamination found in poor-quality fuel.



Length	508.00 mm
Largest OD	301.50 mm
Media Type	NanoNet

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or

non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved