



Product Specification

FS1100

Fuel/Water Separator

Fleetguard® FS1100 fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine.



Thread Diameter	25.40 mm
Anti Drain Back Valve	No
Length	188.16 mm
Largest OD	93.73 mm
Thread Pitch	12 threads Per Inch
Thread Form	Unified National
Gasket OD	88.14 mm
Hydrostatic Burst Minimum	200 PSI
Thread Class	2B
Thread Type	Internal
Flow Direction	Outside In
FREE WATER SEPARATION	95%
Thread Seal Type	Internal
Gasket Inside Diameter	79.76 mm

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved