



Product Specification

FS19591

Fuel/Water Sep Spin-On

Fleetguard® FS19591 fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine. Bottom of shell has internal threads to attach bowl. Bowl has external threads.



Length	215.90 mm
Largest OD	111.00 mm
End 2 OD	107.95 mm
Thread Size	1-14 UNF-2B
EFFICIENCY, TWA BY SAE J 1985	98%
EMULSIFIED WATER SEPARATION	96%
FREE WATER SEPARATION	100%
MICRON RATING BY SAE J 1985	20 micron

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved