



Product Specification

FS19602

Fuel/Water Separator

Fleetguard® FS19602 fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine.



Largest OD	93.73 mm
Length	192.20 mm
Thread Size	13/16-18 UNS-2B
Gasket Inside Diameter	62.48 mm
Gasket OD	71.88 mm
Seam OD	93.47 mm
Standpipe	NO
EFFICIENCY, TWA BY SAE J 1985	98.7%
EMULSIFIED WATER SEPARATION	95%
FREE WATER SEPARATION	95%
MICRON RATING BY SAE J 1985	10 micron

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved