



Product Specification

FS19754

Fuel/Water Separator

Fleetguard® FS19754 premium fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine.



Thread Form	Unified National
Length	218.50 mm
Thread Pitch	14.0 threads Per Inch
Thread Diameter	25.40 mm
Largest OD	110.50 mm
Gasket Inside Diameter	80.00 mm
Gasket OD	91.00 mm
Thread Class	2B
Thread Type	Internal
Outlet #2 Offset, Side View	No
Drain Valve	No
Flow Direction	Outside In
Thread Seal Type	Internal
Water In Fuel Sensor	No

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved