



Product Specification

FS19856

Fuel/Water Separator

Fleetguard® FS19856 premium fuel filter offers optimum protection from contaminants like dirt and water, an engine's biggest enemies, to protect vital fuel system components.



Length / Overall Height	104.02 mm
Largest OD	86.59 mm
End 2 OD	82.30 mm
End 2 ID	20.83 mm
Length	104.14 mm
Media Type	StrataPore
EFFICIENCY, TWA BY SAE J 1985	98.7%
EMULSIFIED WATER SEPARATION	95%
FREE WATER SEPARATION	98%
MICRON RATING BY SAE J 1985	7 micron
Gasket Inside Diameter	20.70 mm

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved