



# Product Specification

## FS19913

Fuel/Water Separator

Fleetguard® FS19913 fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine.



<b>Thread Form</b>	Metric
<b>Thread Pitch</b>	1.50 mm
<b>Thread Diameter</b>	16.00 mm
<b>Largest OD</b>	83.50 mm
<b>Length</b>	183.00 mm
<b>Gasket Inside Diameter</b>	62.00 mm
<b>Gasket OD</b>	70.00 mm
<b>Hydrostatic Burst Minimum</b>	1200 kPa
<b>Thread Class</b>	6H
<b>Thread Type</b>	Internal
<b>Outlet #2 Offset, Side View</b>	No
<b>Drain Valve</b>	No
<b>Flow Direction</b>	Outside In
<b>Thread Seal Type</b>	Internal
<b>Water In Fuel Sensor</b>	No

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved