

FS19926

Fuel/Water Sep Spin-On

Fleetguard® FS19926 fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine.



Thread Pitch 14.0 threads Per Inch

Thread Form Unified National

Length142.00 mmLargest OD96.50 mmThread Diameter25.40 mmGasket Inside Diameter81.00 mmGasket OD91.00 mm

Thread Class 2B

Thread Type Internal
Outlet #2 Offset, Side View No
Drain Valve No

Flow Direction Outside In
Thread Seal Type Internal
Water In Fuel Sensor No

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved