



# Product Specification

## FS20000

Fuel/Water Separator

Fleetguard® FS20000 patented spin-on doser introduces lubricity additive into the fuel. Lubricity-enhancing fuel filtration systems protect components from excessive wear, enhance fuel lubricity for the filter's life, and remove free and emulsified water.



<b>Media Type</b>	StrataPore
<b>Largest OD</b>	93.37 mm
<b>Additive Base</b>	SLOW RELEASE LUBRICITY ENHANCING
<b>Thread Size</b>	1 1/8-16 UN-2B
<b>Length</b>	249.07 mm
<b>Gasket Inside Diameter</b>	62.53 mm
<b>Gasket OD</b>	71.98 mm
<b>Seam OD</b>	92.89 mm
<b>Standpipe</b>	NO
<b>Chemical Additive</b>	SLOW RELEASE LUBRICITY ENHANCING
<b>EFFICIENCY, TWA BY SAE J 1985</b>	98.7%
<b>EMULSIFIED WATER SEPARATION</b>	95%
<b>FREE WATER SEPARATION</b>	95%
<b>MICRON RATING BY SAE J 1985</b>	5 micron

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved