



Product Specification

FS20022

Fuel/Water Sep Spin-On

Fleetguard® FS20022 patented spin-on doser introduces lubricity additive into the fuel. Lubricity-enhancing fuel filtration systems protect components from excessive wear, enhance fuel lubricity for the filter's life, and remove free and emulsified water.



Length	247.37 mm
Thread Size	1 1/8-16 UN-2B
Additive Base	SLOW RELEASE LUBRICITY ENHANCING
Largest OD	93.37 mm
Media Type	StrataPore
Gasket Inside Diameter	62.53 mm
Gasket OD	71.98 mm
Seam OD	93.78 mm
Standpipe	NO
Chemical Additive	SLOW RELEASE LUBRICITY ENHANCING
EFFICIENCY, TWA BY SAE J 1985	96%
EMULSIFIED WATER SEPARATION	90%
FREE WATER SEPARATION	90%
MICRON RATING BY SAE J 1985	25 micron

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved