



Product Specification

HF35338

Hydraulic, Spin-On

Power steering products include Fleetguard® HF35338, Delivered with O-ring gasket 3962133 and Rectangular gasket 3962134. To be used on 'Made in Europe' equipments only.



BPV OPENING DP	No
Thread Form	Unified National
Length	200.00 mm
Largest OD	128.00 mm
Thread Pitch	16.0 threads Per Inch
Hydrostatic Burst Minimum	2000 kPa
Particle Size at Beta 200	12 micron
Particle Size at Beta 75	10 micron
Thread Class	2B
Thread Type	Internal
Flow Direction	Outside In

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved