



Product Specification

HF35345

Hydraulic, Spin-On

Fleetguard® HF35345 hydraulic spin-on filter with cellulose media is designed to help keep your precision hydraulic systems running as intended, providing a solution for various applications. This filter meets or exceeds the equipment OEM quality and performance and is the first aftermarket replacement available on the market today, bringing your operation top-quality performance and an overall unbeatable total cost of ownership.



Thread Form	Unified National
Thread Pitch	12.0 threads Per Inch
Largest OD	96.00 mm
BPV OPENING DP	Yes
Thread Diameter	25.40 mm
Length	181.00 mm
Gasket Inside Diameter	63.00 mm
Gasket OD	70.00 mm
Hydrostatic Burst Minimum	7000 kPa
Particle Size at Beta 200	12 micron
Particle Size at Beta 75	10 micron
Thread Class	2B
Thread Type	Internal
Flow Direction	Outside In

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved