



Product Specification

HF35435

Transmission

Fleetguard® HF35435 hydraulic cartridge filter with cellulose media is designed to help keep your precision hydraulic systems running as intended, providing a solution for various applications. This filter meets or exceeds the equipment OEM quality and performance and is the first aftermarket replacement available on the market today, bringing your operation top-quality performance and an overall unbeatable total cost of ownership.



Length / Overall Height	299.00 mm
Media Type	Others
Largest End ID	42.00 mm
BPV OPENING DP	No
Largest OD	90.00 mm
Length	299.00 mm
Gasket Inside Diameter	1092.20 mm
Gasket OD	90.00 mm
Particle Size at Beta 75	35.0 micron
Flow Direction	Outside In
Pressure Valve	No

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved