



Product Specification

HF6603

Hydraulic, Spin-On

Fleetguard® HF6603 hydraulic spin-on filter with synthetic media is designed to help keep your precision hydraulic systems running as intended, providing a solution for various applications. This filter meets or exceeds the equipment OEM quality and performance and is the first aftermarket replacement available on the market today, bringing your operation top-quality performance and an overall unbeatable total cost of ownership.



BPV OPENING DP	0 kPa
Thread Size	1 1/2-16 UN-2B
Largest OD	93.47 mm
Length	147.83 mm
Gasket Inside Diameter	75.44 mm
Gasket OD	87.63 mm
Seam OD	94.49 mm
Standpipe	NO
TWA MICRON @ BETA=20	1 micron
TWA MICRON @ BETA=200	5 micron
TWA MICRON @ BETA=75	3 micron

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved