



Product Specification

HF6813

Hydraulic, Spin-On

Fleetguard® HF6813 hydraulic spin-on filter with synthetic media is designed to help keep your precision hydraulic systems running as intended, providing a solution for various applications. This filter meets or exceeds the equipment OEM quality and performance and is the first aftermarket replacement available on the market today, bringing your operation top-quality performance and an overall unbeatable total cost of ownership.



Largest OD	124.33 mm
Thread Size	1 1/2-16 UN-2B
Length	297.43 mm
BPV OPENING DP	0 kPa
Gasket Inside Diameter	92.71 mm
Gasket OD	105.92 mm
Seam OD	127.00 mm
Standpipe	NO

TWA MICRON @ BETA=2	3 micron
TWA MICRON @ BETA=20	8 micron
TWA MICRON @ BETA=200	13 micron
TWA MICRON @ BETA=75	12 micron

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved