



Product Specification

LF14001NN

Lube, Spin-On

Fleetguard® LF14001NN premium lube spin-on filter features uses 2-in-1 NanoNet® and StrataPore® media to provide extended service intervals up to 100,000 miles while meeting or exceeding engine requirements. This media manufacturing technology provides the following advantages for our combination filter: higher particle removal efficiency, increased contaminant holding capacity, reduced flow restriction, especially under cold-start conditions, reduced CO2 footprint, and lower total cost of ownership.



Standpipe	No
Anti Drain Back Valve	No
Pressure Valve	No
Gasket OD	120.00 mm
Length	300.00 mm
Media Type	NanoNet
Largest OD	120.00 mm
Thread Diameter	95.00 mm
Thread Pitch	2.50 mm
BPV OPENING DP	No
Thread Form	Metric
Thread Class	7H
Length / Overall Height	300.00 mm
Gasket Inside Diameter	101.40 mm

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved