



Product Specification

LF14009NN

Lube, Spin-On

Fleetguard® LF14009NN premium lube spin-on filter features uses 2-in-1 NanoNet® and StrataPore® media to create a combination filter developed to meet or exceed engine requirements. This media manufacturing technology provides the following advantages for our combination filter: higher particle removal efficiency, increased contaminant holding capacity, reduced flow restriction, especially under cold-start conditions, reduced CO2 footprint, and lower total cost of ownership.



Gasket OD	118.87 mm
Length	300.00 mm
Thread Pitch	12.0 threads Per Inch
BPV OPENING DP	No
Thread Diameter	57.15 mm
Thread Form	Unified National
Media Type	NanoNet
Largest OD	118.31 mm
Standpipe	No
Thread Class	2B

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved