



Product Specification

LF3313

Lube, Full-Flow Spin-On

Fleetguard® LF3313 premium spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.



Gasket Inside Diameter	62.53 mm
Gasket OD	71.98 mm
Largest OD	96.06 mm
BPV OPENING DP	69 kPa
Length	137.08 mm
Thread Size	3/4-16 UNF-2B
Seam OD	96.06 mm
Efficiency	68%
Standpipe	NO
Anti Drain Back Valve	Yes
Length / Overall Height	137.08 mm

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved