



Product Specification

LF3647

Lube, Spin-On

Fleetguard® LF3647 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.



Gasket Inside Diameter	61.50 mm
Gasket OD	71.00 mm
Length	142.50 mm
BPV OPENING DP	Yes
Largest OD	88.50 mm
Thread Form	Metric
Thread Diameter	20.00 mm
Thread Pitch	1.50 mm
Hydrostatic Burst Minimum	1500 kPa
Standpipe	No
Thread Class	6H
Thread Type	Internal
Flow Direction	Outside In

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved