



Product Specification

LF3703

Lube, Spin-On

Fleetguard® LF3703 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.



Gasket OD	95.76 mm
Media Type	Cellulose
Gasket Inside Diameter	80.77 mm
Anti Drain Back Valve	No
Length / Overall Height	146.92 mm
Largest OD	95.76 mm
Thread Size	1 1/2-16 UN-2B
BPV OPENING DP	152 kPa
Length	146.30 mm
Seam OD	93.73 mm
Efficiency	95%
Standpipe	NO

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved