




Product Specification

LF3848

Lube, By-Pass Spin-On

Fleetguard® LF3848 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.



Largest OD	78.00 mm
Length	58.50 mm
Thread Pitch	16.0 threads Per Inch
BPV OPENING DP	Yes
Thread Form	Unified National
Gasket Inside Diameter	62.00 mm
Gasket OD	72.00 mm
Hydrostatic Burst Minimum	1500 kPa
Standpipe	No
Thread Class	2B
Thread Type	Internal
Flow Direction	Outside In

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved