



Product Specification

LF3925

Lube, Spin-On

Fleetguard® LF3925 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.



Gasket OD	62.00 mm
Gasket Inside Diameter	54.00 mm
Thread Diameter	20.00 mm
BPV OPENING DP	Yes
Largest OD	68.50 mm
Thread Pitch	1.50 mm
Thread Form	Metric
Length	67.00 mm
Hydrostatic Burst Minimum	1500 kPa
Standpipe	No
Thread Class	6H
Thread Type	Internal
Flow Direction	Outside In

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved