



Product Specification

LF3977

Lube, Spin-On

Fleetguard® LF3977 cartridge oil filter is environmentally friendly and features technology advances to achieve the high flow rates required by today's modern engine designs.



BPV OPENING DP	No
Thread Pitch	2.00 mm
Largest OD	110.00 mm
Length	212.00 mm
Thread Diameter	30.00 mm
Thread Form	Metric
Gasket Inside Diameter	92.00 mm
Gasket OD	102.00 mm
Standpipe	No
Thread Class	6H
Thread Type	Internal
Hydrostatic Burst Minimum	2000 kPa
Flow Direction	Outside In

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved