



Product Specification

LF680

Lube, Full-Flow Spin-On

Fleetguard® LF680 premium spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.



Thread Size	1 1/2-16 UN-2B
Largest OD	128.98 mm
Length	170.41 mm
BPV OPENING DP	0 kPa
Seam OD	128.93 mm
Efficiency	95%
Standpipe	NO
Length / Overall Height	170.41 mm
Anti Drain Back Valve	No
Gasket OD	0.00 mm
Gasket Inside Diameter	0.00 mm

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved