



Product Specification

LF689

Lube, Full-Flow Spin-On

Fleetguard® LF689 premium spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.



Gasket OD	71.98 mm
Gasket Inside Diameter	62.53 mm
BPV OPENING DP	69 kPa
Thread Size	3/4-16 UNF-2B
Length	107.29 mm
Largest OD	96.20 mm
Seam OD	96.19 mm
Efficiency	95%
Standpipe	NO
Length / Overall Height	107.29 mm
Anti Drain Back Valve	Yes

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved