



Product Specification

LF780

Lube, Spin-On

Fleetguard® LF780 premium spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.



Thread Diameter	18.00 mm
Anti Drain Back Valve	No
Thread Form	Metric
Standpipe	No
Thread Pitch	1.50 mm
Gasket Inside Diameter	62.53 mm
Gasket OD	71.98 mm
Length	88.65 mm
BPV OPENING DP	0 kPa
Thread Size	M18 X 1.5-6H INT
Largest OD	76.99 mm
Seam OD	77.47 mm
Efficiency	95%

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved