

ST1025HH

Hydraulic Filter Head

Fleetguard® ST1025HH filter head is one of multiple inlet and outlet port size options with various by-pass valve settings to meet specific requirements.



Overall Width	75.50
Height	95.00
BPV OPENING DP	No
Length	56.80
Largest Inlet Thread Form	Britisł
Largest Inlet Thread Type	Intern
Largest Outlet Thread Form	Britisł
Largest Outlet Thread Type	Intern
Mounting Orientation	Vertic
Pressure Diagnosis Port	No

75.50 mm 95.00 mm No 56.80 mm British Internal British Internal Vertical This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved