



Product Specification

WF2131

Water, Spin-On

Choose Fleetguard® WF2131 DCA2 water filter with chemicals for coolant system protection that provides filtration and additive reinhibition. DCA2 water filters are designed for use with Fleetcool, Fleetcool EX or similar technology.



Additive Base	DCA2+
COOLANT ADDITIVE FORM	TABLET
Length	137.92 mm
Largest OD	93.73 mm
Thread Size	11/16-16 UN-2B
Gasket Inside Diameter	62.74 mm
Gasket OD	72.39 mm
Seam OD	93.78 mm
Chemical Additive	DCA2+

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved