

WF2138

Water, Spin-On

Choose Fleetguard® WF2138 DCA2 water filter with chemicals for coolant system protection that provides filtration and additive reinhibition. DCA2 water filters are designed for use with Fleetcool, Fleetcool EX or similar technology.



Largest OD 93.83 mm

Thread Size M16 X 1.5-6H INT

Length 138.05 mm

COOLANT ADDITIVE FORM TABLET

Additive Base DCA2+

Gasket Inside Diameter 62.53 mm

Gasket OD 71.98 mm

Seam OD 93.78 mm

Chemical Additive DCA2+

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved