

=	
_	Park(er

Home

Products

Support

Industries

Services

Solutions

Where to Buy

PEACH® DYNASEP™ PCHG & EZ-PCHG Gas Filter-Separator Cartridge | #00-031735



Local Contact

Parker Sales Company UK

Tachbrook Park Drive

Tachbrook Park

CV34 6TU

Phone

+44 (0)1926 317878

Get your Parker account Today!

Create one account to manage everything you do with Parker, from your shopping preferences to your application access.

Register now

PCHG-336-C

♦ Share / Email

Technical Specifications

Maximum Pressure Differential:

30 PSID

pH Range:

3-9

Nominal Inside Diameter:

3"

Core Material:

Tin-Plated Steel

Nominal Outside Diameter:

4.5"

End Cap Material:

Polyester

Seal Material:

Integral PEACH end serves as seal

Cartridge Length:

36'

Maximum Operating Temperature:

240 F

End Cap Configuration:

DOE - Double Open End

Product Series:

PCHG

Filter Material:

Polyester

Body Material:



N/A Flow Direction: Outside-to-inside 15 PSID

Changeout Pressure Differential:

Filter Construction:

PEACH Depth

Micron Rating:

Model Number:

ELMT PCHG-336-C

Division:

Industrial Process Filtration Division

Brand:

PECO

Filter Construction:

PEACH Depth

Changeout Pressure Differential:

15.0

Flow Direction:

Outside-to-inside

Quantity per Box:

4.0

Product Type:

Filter Cartridge

Industry:

Oil and Gas

Application:

Gas Particulate Filtration

Technology:

Filtration



Safety Warning

Item Information

The PEACH® DYNASEP™ PCHG & EZ-PCHG Gas Filter-Separator cartridges are a great choice for removing deformable and shear sensitive contaminants from natural gas streams.

The PEACH® DYNASEP™ PCHG can be used in the PECO Series 75 and Series 85 vessels, as well as in several competitor filter-separator vessels. The synthetic construction allows for an environmentally friendly product and an excellent upgrade option to traditional fiberglass cartridges. The Series PCHG is made using the patented PEACH process which provides increased flow, high efficiency, and effective removal of contaminants. This equates to increased operational life, fewer change-outs, reduced maintenance, and reduced costs.

The PEACH DYNASEP® EZ-PCHG can be used in PECO Series 75HTL and 75VTL Titan PuraSep® vessels. The unique end cap design requires no tools, allowing for easy installation & removal during change-outs. The inclusion of EZ-Align® ensures a positive seal and prevents cartridge sagging. The unprecedented multidirectional, tortuous flow path creates a true gradient depth filter that increases residence time for contaminant removal while maintaining porosity and permeability through the media. PEACH cartridges have

become a go-to filter used by consumers who have seen the benefits of longer on-stream service life between change-outs and improved effluent gas quality.

INDUSTRIES

· Oil & Gas

FEATURES/BENEFITS

- Upgraded design from traditional fiberglass "FG" style cartridge
- PEACH® technology
- Used to remove solid contaminant from a natural gas stream while also preparing liquid droplets to be coalesced by second stage mist extraction device
- Removes contaminants such as asphaltenes, coal fines, dirt, iron sulfides, molecular sieve dust, pipe scale, salt, sand, wear metals

APPLICATIONS

- City Gate
- · Compressor & Turbine Suction
- Contact Towers (Inlet & Overhead)
- · Custody Transfer Fuel Gas
- · Gas Distribution
- · Gas Storage
- Gas Transmission
- · Gas Treating & Dehydration
- · Landfill Gas
- M&R Stations
- · Plant Entrance Gas
- Show Less

CAD Drawings + Files

No CAD files available



Parker Sales Company UK

+44 (0)1926 317878

psc.uk.webform@support.parker.com

- + Company Information
- + Global Operations



+ Help & Support		
+ Follow Us:		

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS

