

<u>Home</u>

Products

Support PEACH® DYNASEP[™] PCHG & EZ-PCHG Gas Filter-Separator Cartridge | #00-031736

Services I≡ <u>View Series Page</u> Solutions

Where to Buy



Z

Local Contact

Parker Sales Company UK

Tachbrook Park Drive

Tachbrook Park

Warwick

United Kingdom

CV34 6TU

Phone

+44 (0)1926 317878

	Get your Parker account Today!
Home Create one account to manage	e everything you do with Parker, from your shopping preferences to your
Products	application access.
<u>Support</u>	Register now
Industries PCHG-372-C	
Share / Email	
Solutions	
Technicates Speece in the second seco	
Maximum Pressure Differential: 30 PSID	
pH Range: 3-9	
Nominal Inside Diameter: 3"	
Cartridge Length: 72"	
Core Material: Tin-Plated Steel	
Nominal Outside Diameter: 4.5"	
End Cap Material: Polyester	
Seal Material: Integral PEACH end serves as seal	
Maximum Operating Temperature: 240 F	
End Cap Configuration: DOE - Double Open End	
Product Series: PCHG	
Filter Material: Polyester	
Body Material: N/A	
Flow Direction: Outside-to-inside	
Changeout Pressure Differential: 15 PSID	
Filter Construction: PEACH Depth	

Mid Model Number HOME CHG-372-C **Division:** Industrial Process Filtration Division Brand: PECO <u>Support</u> Filter Construction: PEACH Depth Industries Changeout Pressure Differential: 15.0 Services Outside-to-inside Solutions Box: 4.0 PWheterto Buy Filter Cartridge Industry: Oil and Gas Application: **Gas Particulate Filtration** Technoloav: Filtration

A Safety Warning

Item Information

The PEACH® DYNASEP[™] PCHG & EZ-PCHG Gas Filter-Separator cartridges are a great choice for removing deformable and shear sensitive contaminants from natural gas streams.

The PEACH® DYNASEP[™] PCHG can be used in the PECO Series 75 and Series 85 vessels, as well as in several competitor filter-separator vessels. The synthetic construction allows for an environmentally friendly product and an excellent upgrade option to traditional fiberglass cartridges. The Series PCHG is made using the patented PEACH process which provides increased flow, high efficiency, and effective removal of contaminants. This equates to increased operational life, fewer change-outs, reduced maintenance, and reduced costs.

The PEACH DYNASEP® EZ-PCHG can be used in PECO Series 75HTL and 75VTL Titan PuraSep® vessels. The unique end cap design requires no tools, allowing for easy installation & removal during change-outs. The inclusion of EZ-Align® ensures a positive seal and prevents cartridge sagging. The unprecedented multidirectional, tortuous flow path creates a true gradient depth filter that increases residence time for contaminant removal while maintaining porosity and permeability through the media. PEACH cartridges have become a go-to filter used by consumers who have seen the benefits of longer on-stream service life between change-outs and improved effluent gas quality.

INDUSTRIES • Oil & Gas

FEATURES/BENEFITS

h traditional fiberglass "FG" style cartridge



the contaminant from a natural gas stream while also preparing liquid droplets to be coalesced

by second stage mist extraction device • Removes contaminants such as asphaltenes, coal fines, dirt, iron sulfides, molecular sieve dust, pipe scale, salt, sand, wear metals

Products

APPLICATIONS

- ·<u>Support</u>
- Compressor & Turbine Suction
- Contact Towers (Inlet & Overhead)
 Industries
 Custody Transfer Fuel Gas
- Gas Distribution
- .<u>Services</u>ae
- Gas Transmission
- · Soluitientis g & Dehydration
- Landfill Gas
- M&R Stations Plant Entrance Gas

Show Less

CAD Drawings + Files

No CAD files available



Parker Sales Company UK

<u>+44 (0)1926 317878</u>

psc.uk.webform@support.parker.com

- + Company Information
- + Global Operations
- + Help & Support
- + Follow Us :



ENGINEERING YOUR SUCCESS.

Η	0	m	<u>1e</u>

Products

<u>Support</u>

Industries

<u>Services</u>

Solutions

Where to Buy