

Home

Products

Support
PEACH® DYNASEP™ PCHG & EZ-PCHG Gas Filter-Separator
Cartridge | #00-031738

Services

∀iew Series Page

Solutions

Where to Buy



Local Contact

Parker Sales Company UK

Tachbrook Park Drive

Tachbrook Park

Warwick

United Kingdom

CV34 6TU

Phone

+44 (0)1926 317878





Get your Parker account Today!

Home

Create one account to manage everything you do with Parker, from your shopping preferences to your application access.

Products

Support

Register now

<u>Industries</u>

PCHG-372-10

Services

Share / Email

Solutions

TWome and Spley ifications

Model Number:

ELMT PCHG-372-10

Maximum Pressure Differential:

30 PSID

pH Range:

3-9

Nominal Inside Diameter:

3

Cartridge Length:

72"

Core Material:

Tin-Plated Steel

Nominal Outside Diameter:

4.5"

End Cap Material:

Polyester

Seal Material:

Integral PEACH end serves as seal

Maximum Operating Temperature:

240 F

End Cap Configuration:

DOE - Double Open End

Product Series:

PCHG

Filter Material:

Polyester

Body Material:

N/A

Flow Direction:

Outside-to-inside

Changeout Pressure Differential:

15 PSID





Home

Division:

Industrial Process Filtration Division **Products**

Brand:

<u>Support</u> Filter Construction:

PEACH Depth

Industries Changeout Pressure Differential:

Services ion:

Outside-to-inside

Solutions Box:

PWhererto Buy

Filter Cartridge

Industry:

Oil and Gas

Application:

Gas Particulate Filtration

Technology:

Filtration



Item Information

The PEACH® DYNASEP™ PCHG & EZ-PCHG Gas Filter-Separator cartridges are a great choice for removing deformable and shear sensitive contaminants from natural gas streams.

The PEACH® DYNASEP™ PCHG can be used in the PECO Series 75 and Series 85 vessels, as well as in several competitor filter-separator vessels. The synthetic construction allows for an environmentally friendly product and an excellent upgrade option to traditional fiberglass cartridges. The Series PCHG is made using the patented PEACH process which provides increased flow, high efficiency, and effective removal of contaminants. This equates to increased operational life, fewer change-outs, reduced maintenance, and reduced costs.

The PEACH DYNASEP® EZ-PCHG can be used in PECO Series 75HTL and 75VTL Titan PuraSep® vessels. The unique end cap design requires no tools, allowing for easy installation & removal during change-outs. The inclusion of EZ-Align® ensures a positive seal and prevents cartridge sagging. The unprecedented multidirectional, tortuous flow path creates a true gradient depth filter that increases residence time for contaminant removal while maintaining porosity and permeability through the media. PEACH cartridges have become a go-to filter used by consumers who have seen the benefits of longer on-stream service life between change-outs and improved effluent gas quality.

INDUSTRIES

· Oil & Gas



- h traditional fiberglass "FG" style cartridge
- tontaminant from a natural gas stream while also preparing liquid droplets to be coalesced
- by second stage mist extraction device **Home** Removes contaminants such as asphaltenes, coal fines, dirt, iron sulfides, molecular sieve dust, pipe scale, salt, sand, wear metals

Products

APPLICATIONS

- ·Support
- · Compressor & Turbine Suction
- Contact Towers (Inlet & Overhead)
 Custody Transfer Fuel Gas
- Gas Distribution
- · Services de
- Gas Transmission
- · Sosuitioning & Dehydration
- · Landfill Gas
- M&R Stations Where to Buy Plant Entrance Gas
- Show Less

CAD Drawings + Files

No CAD files available



Parker Sales Company UK

+44 (0)1926 317878

psc.uk.webform@support.parker.com

- + Company Information
- + Global Operations
- + Help & Support
- + Follow Us:







<u>Home</u>

Products

<u>Support</u>

<u>Industries</u>

<u>Services</u>

Solutions

Where to Buy

