



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

Home / Products / Filters, Collectors, Separators / Replacement Filter Elements... / Natural Gas Filter Elements / PEACH® DYNASEP™ PCHG & EZ-P... / 00-032113

# PEACH® DYNASEP™ PCHG & EZ-PCHG Gas Filter-Separator Cartridge

Part #: 00-032113



PCHG-336-SCW

[View Series Page](#) [Share / Email](#) [Print](#)

## Technical Specifications

Micron Rating:	0.3	Flow Direction:	Outside-to-inside
pH Range:	3-9	Changeout Pressure Differential:	15 PSID
Maximum Pressure Differential:	30 PSID	Filter Construction:	PEACH Depth
Nominal Inside Diameter:	3"	Model Number:	ELMT PCHG-336-SCW
Core Material:	Tin-Plated Steel	Division:	Industrial Process Filtration Division
End Cap Material:	Polyester	Brand:	PECO
Nominal Outside Diameter:	4.5"	Filter Construction:	PEACH Depth
Seal Material:	Integral PEACH end serves as seal	Changeout Pressure Differential:	15.0
Cartridge Length:	36"	Flow Direction:	Outside-to-inside
Maximum Operating Temperature:	240 F	Quantity per Box:	4.0
End Cap Configuration:	DOE - Double Open End	Product Type:	Filter Cartridge
Body Material:	N/A	Industry:	Oil and Gas
Product Series:	PCHG	Application:	Gas Particulate Filtration
Filter Material:	Polyester	Technology:	Filtration

[Safety Warning](#)

## Item Information

The PEACH® DYNASEP™ PCHG & EZ-PCHG Gas Filter-Separator cartridges are a great choice for removing deformable and shear sensitive contaminants from natural gas streams.



The PEACH® DYNASEP™ PCHG can be used in the PECO Series 75 and Series 85 vessels, as well as in several competitor filter-separator vessels.

The synthetic construction allows for an environmentally friendly product and an excellent upgrade option to traditional fiberglass cartridges. The Series PCHG is made using the patented PEACH process which provides increased flow, high efficiency, and effective removal of contaminants. This equates to increased operational life, fewer change-outs, reduced maintenance, and reduced costs.

The PEACH DYNASEP® EZ-PCHG can be used in PECO Series 75HTL and 75VTL Titan PuraSep® vessels. The unique end cap design requires no tools, allowing for easy installation & removal during change-outs. The inclusion of EZ-Align® ensures a positive seal and prevents cartridge sagging. The unprecedented multidirectional, tortuous flow path creates a true gradient depth filter that increases residence time for contaminant removal while maintaining porosity and permeability through the media. PEACH cartridges have become a go-to filter used by consumers who have seen the benefits of longer on-stream service life between change-outs and improved effluent gas quality.

#### INDUSTRIES

- Oil & Gas

#### FEATURES/BENEFITS

- Upgraded design from traditional fiberglass "FG" style cartridge
- PEACH® technology
- Used to remove solid contaminant from a natural gas stream while also preparing liquid droplets to be coalesced by second stage mist extraction device
- Removes contaminants such as asphaltenes, coal fines, dirt, iron sulfides, molecular sieve dust, pipe scale, salt, sand, wear metals

#### APPLICATIONS

- City Gate
- Compressor & Turbine Suction
- Contact Towers (Inlet & Overhead)
- Custody Transfer Fuel Gas
- Gas Distribution
- Gas Storage
- Gas Transmission
- Gas Treating & Dehydration
- Landfill Gas
- M&R Stations
- Plant Entrance Gas

## CAD Drawings + Files -

No CAD files available

## Related Documents +



**Parker Sales Company UK**

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)  
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



