



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

Home / Products / Filters, Collectors, Separators / Replacement Filter Elements... / Natural Gas Filter Elements / PEACH® DYNASEP™ PCHG & EZ-P... / 00-032160

PEACH® DYNASEP™ PCHG & EZ-PCHG Gas Filter-Separator Cartridge

Part #: 00-032160



PCHG-336- 5

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

pH Range:	3-9	Filter Material:	Polyester
Maximum Pressure Differential:	30 PSID	Flow Direction:	Outside-to-inside
Nominal Inside Diameter:	3"	Changeout Pressure Differential:	15 PSID
Core Material:	Tin-Plated Steel	Filter Construction:	PEACH Depth
End Cap Material:	Polyester	Division:	Industrial Process Filtration Division
Nominal Outside Diameter:	4.5"	Brand:	PECO
Seal Material:	Integral PEACH end serves as seal	Filter Construction:	PEACH Depth
Cartridge Length:	36"	Changeout Pressure Differential:	15.0
Maximum Operating Temperature:	240 F	Flow Direction:	Outside-to-inside
End Cap Configuration:	DOE - Double Open End	Quantity per Box:	4.0
Micron Rating:	5	Product Type:	Filter Cartridge
Body Material:	N/A	Industry:	Oil and Gas
Model Number:	ELMT PCHG-336- 5	Application:	Gas Particulate Filtration
Product Series:	PCHG	Technology:	Filtration

[Safety Warning](#)

Item Information

The PEACH® DYNASEP™ PCHG & EZ-PCHG Gas Filter-Separator cartridges are a great choice for removing deformable and shear sensitive contaminants from natural gas streams.



The PEACH® DYNASEP™ PCHG can be used in the PECO Series 75 and Series 85 vessels, as well as in several competitor filter-separator vessels.

The synthetic construction allows for an environmentally friendly product and an excellent upgrade option to traditional fiberglass cartridges. The Series PCHG is made using the patented PEACH process which provides increased flow, high efficiency, and effective removal of contaminants. This equates to increased operational life, fewer change-outs, reduced maintenance, and reduced costs.

The PEACH DYNASEP® EZ-PCHG can be used in PECO Series 75HTL and 75VTL Titan PuraSep® vessels. The unique end cap design requires no tools, allowing for easy installation & removal during change-outs. The inclusion of EZ-Align® ensures a positive seal and prevents cartridge sagging. The unprecedented multidirectional, tortuous flow path creates a true gradient depth filter that increases residence time for contaminant removal while maintaining porosity and permeability through the media. PEACH cartridges have become a go-to filter used by consumers who have seen the benefits of longer on-stream service life between change-outs and improved effluent gas quality.

INDUSTRIES

- Oil & Gas

FEATURES/BENEFITS

- Upgraded design from traditional fiberglass "FG" style cartridge
- PEACH® technology
- Used to remove solid contaminant from a natural gas stream while also preparing liquid droplets to be coalesced by second stage mist extraction device
- Removes contaminants such as asphaltenes, coal fines, dirt, iron sulfides, molecular sieve dust, pipe scale, salt, sand, wear metals

APPLICATIONS

- City Gate
- Compressor & Turbine Suction
- Contact Towers (Inlet & Overhead)
- Custody Transfer Fuel Gas
- Gas Distribution
- Gas Storage
- Gas Transmission
- Gas Treating & Dehydration
- Landfill Gas
- M&R Stations
- Plant Entrance Gas

CAD Drawings + Files



Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com

[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



