

Products

Support

Itante stress ucts / Filters, Collectors, Separa... / Replacement Engine and Mobi... / Hydraulic Filter Elements / Replacement Elements - High... / 1111214151-01

Replacement Elements - High Pressure In-Line Filter 70/70 Eco Series

Solutions Part #: 1111214151-01

Where to Buy







High pressure inline hydraulic oil filter series is a proven filter concept, up to 500l/min and pressures up to 420 bar.

View Series Page **≔**

View Catalog(s)

Share / Email

Print =

Technical Specifications

Division: Hydraulic and Industrial Process Filtration EMEA

For Use With: 70 series length 1

Brand: Parker

Filter Element Type: 02QH High collapse

Technology: Filtration Micron Rating: 2 µm Seal Material: **EPDM**

Product Type: Hydraulic Oil Filter Replacement Elements

Lenath: 115 mm **Product Series:** 70/70 Eco Series End Cap Material: Tin plated steel

Mining

Material handling Construction

Industry: Marine Power Generation

Industrial Machinery

Injection Moulding

Options: Epoxy glued end caps

> **Drilling machines** Dumpers Hydraulic power units Mobile cranes Reach stackers

Container handling equipment

Cranes

Application: Excavators Crushing machines

Propulsion systems Deck machinery Wind turbines Hydropower

Suitable for use with mineral and vegetable oils, and

some synthetic oils.

Operating Pressure: 420 bar (350 bar Length 4) Maximum.

Operating

For Fluid Type:

Temperature:

⚠ Safety Warning

Item Information

The 70/70 Eco Series of high pressure filters are designed to satisfy demanding applications in the mobile and industrial markets. With multiple mounting options, this high pressure filter series is right filter for many applications. The 70/70 Eco Series filter series has a wide range of high capacity and low initial differential pressure elements, including a no metal content Eco element, offering excellent protection to system components

The 70/70 Eco Serie offers several bowl lengths to secure the lowest possible pressure drop for each application. For critical applications such as servo or proportional controls, a no bypass high strength element combination ensures maximum protection.

The low hystereis differential pressure indicator fitted to this series is unrivalled in its performance.



- Mobile drive system
 Injection moulding
 Servo controls
 Broducts

- Machine tools
 Supportal power units

Haduskriess formation or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

ட்டிற்ற rawings + Files	+
<u>Solutions</u>	
Related Documents	+



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

+ Company Information + Global Operations + Help & Support + Follow Us:

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS



<u>Home</u>

Products

<u>Support</u>

Industries

Services

Solutions

Where to Buy